


APE1 SERIES ENERGY STAR® PRO-STYLE RANGE HOOD



Designed to meet the performance needs of today's higher BTU conventional cooking appliances and consumers' desire for ENERGY STAR® qualification.

FEATURES

- Professional styling in Stainless Steel only
- Available in 30" width only
- Infinite speed rotary control with solid state blower memory and separate on/off switch
- Two-position light switch for "bright" or "night-light" illumination
- Single 26W GX24Q-3 Fluorescent lamp with 4W C-7 night light (included)
- High efficiency dual centrifugal blower with resilient antivibration motor mounts
- Broan Heat Sentry[™] automatically turns blower to high speed when excess cooking heat is detected
- Two washable, micromesh aluminum grease filters with anitmicrobial protection that inhibits the formation of odorproducing bateria and protects filter from discoloration
- Hemmed bottom for safety and good looks
- Damper/duct connector included
- Non-Ducted Recirculation Kit NDK358 Series
 - ENERGY STAR® qualification is void if hood is used in a non-ducted application
- Replacement filters (package of 2):
 - Grease <u>with</u> anitmicrobial protection 97017456 (BPAPFA)
 - Grease <u>without</u> anitmicrobial protection 97017455 (BPRPFA)
 - Non-Ducted 97007662 (88F)
- · For indoor use only

SPECIFICATIONS

		CFM		SONES		DUCT	
AMPS	ΗZ	MAX.	NORM.	MAX.	NORM.	DUCT	
120 1.8	60	440	200	7.0	0.7	3¼" x 10" (Horiz.)	
		440	200	7.0	0.9	3¼" x 10" (Vert.)	
			AMPS HZ MAX.	AMPS HZ MAX. NORM. 1.8 60 440 200	AMPS HZ MAX. NORM. MAX. 18 60 440 200 7.0	AMPS HZ MAX. NORM. MAX. NORM. 18 60 440 200 7.0 0.7	







HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in a state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

TYPICAL SPECIFICATION

Range hood shall be Broan APE1 Series.

Unit shall have a backdraft damper and be ducted vertically (horizontally) to the outside.


Unit shall have washable micromesh aluminum filters with special antimicrobial protection.

Unit shall have a permanently lubricated, dual centrifugal blower resiliently mounted and controlled with an infinite speed, solid state control. RPM not to exceed 1618.

Hood shall have an infinite speed rotary control with memory and a separate, two-position light switch. Sides shall be straight and bottom hemmed - with no sharp edges. Stainless steel shall be 24-gauge, 430 series.

Air delivery shall be no less than 440 cfm and sound levels no greater than 7.0 Sones. All air and sound ratings shall be certified by HVI.

Unit shall be U.L. and cU.L. listed and ENERGY STAR® qualified.



Broan-NuTone LLC	Hartford, Wisconsin	www.broan.com	800-558-1711
			_

REFERENCE	QTY.	REMARKS	Project	
			Location	
			Architect	
			Engineer	
			Contractor	
			Submitted by	Date