

ACNC/TotalPlex®

DP28-NxT

Door Station (T-Series)

DESCRIPTION





The **DP28-NIT** and **DP28-NWT** are the basic Door Station models. Manufactured in sturdy ivory or white polymer, these Door Stations look great anywhere they are placed. These units provide standard door-to-phone communication when used with the **DP28-C***. Installation and operation are very simple. The **DP28-NIT** and **DP28-NWT** are also available in kits with the DP28-C as the **DP28-IT** and **DP28-WT**.

*DP28-C only included in kits


DP28-NIT

DP28-NWTWhite Polymer

Ivory Polymer

FEATURES

- Manufactured in sturdy polymer
- Available in Ivory and White finishes
- Mounts easily on most surfaces including fences and gates
- Installs with a single pair of wires
- Optional Door Station Awning for protection from the environment
- No external power required: power drawn from connected Door Station Controller



APPLICATIONS

- Communicate with people at a door, gate, or any other entrance way where Door Station is present
- Use in conjunction with the DP29-CI to activate external trigger devices (e.g. door chimes, cameras, lights...) with the Door Station
- Use in conjunction with the DP29-SW to open electronically locked doors or gates with the phone
- Use as extra Door Station to any Door Station Kit

SPECIFICATIONS

Power:

N/A

Dimensions:

• 3.875" x 5.125" x 1.25"

Shipping Weight:

• 1.0 lbs


Speaker:

• Frequency Response: 400~2.8kHz

Impedance: 8ΩPeak Power: 0.25W

Microphone:

• Frequency Response: 200~6.8kHz



HTTP://WWW.HOMEPHONE.COM

EMAIL: INFO@HOMEPHONE.COM

Tel: (630) 241-2800 Fax: (630) 241-2820