

DP38-NxN

Door Station (N-Series)

DESCRIPTION







DP38-NBKNBlack NUTONE size



DP38-NBZN
Bronze NUTONE size



DP38-NSNAluminum NUTONE size

The N-Series Door Station models include DP38-NBN, DP38-NBKN, DP38-NBZN, and DP38-NSN. These units provide standard door-to-phone communication when used with the DP28-C*. A new design not only brings great new looks, but great new additions as well. A discrete slot is available for an optional third-party 14mm pinhole camera and the weather-proof back box provides quality protection and durability for your unit. All N-Series mount into any standard NUTONE's (IR-6 or IA-70) box as flush or surface mounts. Colors are available in 4 anodized finishes: brass, black, bronze, and aluminum. These Door Stations are also available in kits with the DP28-C as the DP38-BN, DP38-BKN, DP38-BZN, and DP38-SN.


*DP28-C not included

FEATURES

- Manufactured in aluminum with anodized Brass, Black, Bronze, and Aluminum finishes
- Mounts into any standard NUTONE's (IR-6 or IA-70) box as a flush or surface mount
- All back boxes are manufactured in steel with black powder-coating finish and provides superior protection from the elements
- No external power required: power drawn from connected Door Station Controller (DP28-C)
- LED button lights up when the Door Station is active
- Discrete slot available for optional 3rd party cameras

APPLICATIONS

- Communicate with people at a door, gate, or any other entrance way where Door Station is present
- Can be placed at:
 - o Front/Rear Entrances
 - o Remote Entryways
 - o Marine Docks
 - o Delivery Docks
 - Secured Facilities
- Senior Housing
- Disabled Housing
- o Apartment
 - Complex



- Use in conjunction with the DP29-CI to activate external trigger devices (e.g. door chimes, cameras, lights...) with the Door Station
- Use in conjunction with the DP29-SW to open electronically locked doors or gates with the phone
- Use in conjunction with the DP38-T to answer your door with your cellphone
- Mount a third-party 14mm security camera in the camera slot to see who is at your door
- Use as extra Door Station to any Door Station Kit



DP38-NxN

Door Station (N-Series)

SPECIFICATIONS

Power:

• Circuit Board: no external power required

• Camera: see third-party camera specifications

Dimensions:

• 4.75" x 6.375" x 1.625"

Shipping Weight:

• 2.0 lbs


Speaker:

• Frequency Response: 400~2.8kHz


Impedance: 8ΩPeak Power: 0.25W


Microphone:

• Frequency Response: 200~6.8kHz



MOUNTING





HTTP://WWW.HOMEPHONE.COM

EMAIL: INFO@HOMEPHONE.COM Tel: (630) 241-2800 Fax: (630) 241-2820